

Linear Unit CTJ 110

The CTJ series includes linear units with a toothed belt drive and two parallel, integrated, zero-backlash rail guides. In the linear units CTJ is used a pre-tensioned steel reinforced AT polyurethane timing toothed belt. In conjunction with a zero-backlash drive pulley high moments with alternating loads with good positioning accuracy, low wear and low noise can be realized.

The in the profile slot driving timing belt, protects all the parts in the profile from dust and other contaminations. Re-lubrication can be done through maintenance holes on the side of the profile.

Dimensions in mm.



Modulus of Elasticity: $E = 70000 \text{ N / mm}^2$

Operating Temperature (°C): 0 ~ +60 For operating temperature out of the presented range, please contact Rollco.

Duty Cycle: 100%

Max. Acceleration (m/s²): 70


Max. Travel Speed (m/s): 6




1. Drive block with pulley
2. Aluminum cover
3. Carriage, with built in magnets
4. AT polyurethane toothed belt with steel tension cords
5. Aluminium profile - hard anodized
6. Two integrated linear ball guideways
7. Central lubrication port, both sides
8. Tension end with integrated belt tensioning system

Deflection of the linear unit

CTJ 110



- ① The linear units do not include any safety stroke. Absolute stroke = Effective stroke + 2 x safety stroke




- ① Journal with or without keyway ② All dimensions in mm. Drawings scales are not equal

Deflection of the linear unit


CTJ

Fixed - fixed mounting

Fixed - free mounting




δ	Maximum deflection of the linear unit [mm]
δ_{\max}	Maximum permissible deflection of the linear unit [mm]
F	Applied force [N]
L_p	Unsupported profile length [mm]





The maximum permissible deflection f_{\max} must not be exceeded. In the case that maximum deflection f exceeds the maximum permissible deflection f_{\max} additional profile supports are needed.

- ③ The linear units do not include any safety stroke. Absolute stroke = Effective stroke + 2 x safety stroke




- ① Journal with or without keyway ② All dimensions in mm. Drawings scales are not equal

- ③ The linear units do not include any safety stroke. Absolute stroke = Effective stroke + 2 x safety stroke



- ① Journal with or without keyway ② All dimensions in mm. Drawings scales are not equal



Linear Unit CTJ 110




Defining of the linear unit length

$L = \text{Effective stroke} + 2 \times \text{Safety stroke} + L_v + 25 \text{ mm}$


$L_{\text{total}} = L + 126 \text{ mm}$



Connection plate



General data



For length/stroke over the stated value, please contact Rollco. Values for max. stroke are not valid for double carriage (equation of defining the linear unit length for particular size of the linear unit needs to be used).

For minimum stroke below the stated value, please contact Rollco.

Recommended values of loads

All the data of static and dynamic moments and load capacities stated are theoretical without considering any safety factor. The safety factor depends on the application and its requested safety.


We recommend a minimum safety factor ($f_s = 5.0$).

Designation	Carriage Length L_v (mm)	Dynamic Moment M_x (Nm)	Dynamic Moment M_y (Nm)	Dynamic Moment M_z (Nm)	Dynamic Load Capacity C (N)
CTJ 110 S	170	610	118	235	19800
CTJ 110 L	215	1225	1680	1680	39600

Designation	Static Load Capacity C_0 (N)	Max. Permissible Loads Forces F_{py} (N)	Max. Permissible Loads Forces F_{pz} (N)	Max. Permissible Loads Moments M_{px} (Nm)	Max. Permissible Loads Moments M_{py} (Nm)	Max. Permissible Loads Moments M_{pz} (Nm)
CTJ 110 S	35000	6470	8390	260	90	90
CTJ 110 L	70000	13070	18820	525	880	550

Designation	Moved Mass (kg)	Max. Repeatability (mm)	Max. Length L_{max} (mm)	Max. Stroke (mm)	Min. Stroke (mm)
CTJ 110 S	0.64	± 0.08	6000	5805	40
CTJ 110 L	0.98	± 0.08	6000	5760	40

General data double carriage



A - Distance between carriages.

Recommended values of loads


All the data of static and dynamic moments and load capacities stated are theoretical without considering any safety factor. The safety factor depends on the application and its requested safety.

We recommend a minimum safety factor ($f_s = 5.0$).

Designation	Carriage version	Dynamic Load Capacity C (N)	Static Load Capacity C0 (N)	Dynamic Moment Mx (Nm)	Dynamic Moment My (Nm)
CTJ 110 S	S2	39600	70000	1220	$19.8 \times A$ (mm)
CTJ 110 L	S2	39600	70000	1220	$19.8 \times A$ (mm)

Designation	Dynamic Moment Mz (Nm)	Max. Permissible Loads Forces Fpy (N)	Max. Permissible Loads Forces Fpz (N)	Max. Permissible Loads Moments Mpx (Nm)	Max. Permissible Loads Moments Mpy (Nm)	Max. Permissible Loads Moments Mpz (Nm)
CTJ 110 S	$19.8 \times A$ (mm)	12940	16770	520	$8.4 \times A$ (mm)	$6.5 \times A$ (mm)
CTJ 110 L	$19.8 \times A$ (mm)	12940	16770	520	$8.4 \times A$ (mm)	$6.5 \times A$ (mm)

Drive data



The stated values are for strokes up to 500 mm.
No load torque value increases with stroke elongation.

Max. acceleration (m/s²): 70

For acceleration over the stated value, please contact Rollco.


Mass calculation does not include mass of motor, reduction gear, switches and clamps.

Abs. stroke	Absolute stroke [mm]
A	Distance between carriages [mm]
nc	Number of carriages

Designation	Max. Travel Speed (m/s)	No Load Torque (Nm)	Pulley Drive Ratio (mm/rev)	Pulley Diameter	Belt Type
CTJ 110 S	6	0.98 × nc	120	38.2	AT 5
CTJ 110 L	6	1.00 × nc	120	38.2	AT 5

Designation	Belt Width	Max. Force Transmitted by Belt (N)	Specific Spring Constant Cspec (N)	Max. Drive Torque (Nm)	Planar Moment of Inertia Iy (cm ⁴)	Planar Moment of Inertia Iz (cm ⁴)
CTJ 110 S	50	820	960000	15.7	31.1	217.2
CTJ 110 L	50	820	960000	15.7	31.1	217.2

Mass and Mass moment



The stated values are for strokes up to 500 mm.
No load torque value increases with stroke elongation.

Max. acceleration (m/s²): 70

For acceleration over the stated value, please contact Rollco.

Mass calculation does not include mass of motor, reduction gear, switches and clamps.

Abs. stroke	Absolute stroke [mm]
A	Distance between carriages [mm]
nc	Number of carriages

Designation	Mass of Linear Unit (kg)	Mass Moment of Inertia (10 ⁻⁵ kg m ²)	Planar Moment of Inertia I _y (cm ⁴)	Planar Moment of Inertia I _z (cm ⁴)	Moved Mass (kg)
CTJ 110 S	$3.6 + 0.0072 \times (\text{Abs. Stroke} + (\text{nc} - 1) \times A) + 0.64 \times (\text{nc} - 1)$	$36 + 0.0125 \times (\text{Abs. Stroke} + (\text{nc} - 1) \times A) + 23.3 \times (\text{nc} - 1)$	31.1	217.2	0.64
CTJ 110 L	$4.2 + 0.0072 \times (\text{Abs. Stroke} + (\text{nc} - 1) \times A) + 0.98 \times (\text{nc} - 1)$	$49 + 0.0125 \times (\text{Abs. Stroke} + (\text{nc} - 1) \times A) + 35.8 \times (\text{nc} - 1)$	31.1	217.2	0.98

Designation	No Load Torque (Nm)
CTJ 110 S	$0.98 \times \text{nc}$
CTJ 110 L	$1.00 \times \text{nc}$