Lubrication syringe

Lubrication syringes are available in many different possible combinations, depending on type of grease (or oil) and the size of the needle pre-defined. A selection of these are presented in the table below. For other types, please contact Rollco.



Lubrication grease:
00 For general applications
01 For low-friction, low-noise applications
02 For clean room applications
03 For clean room and vacuum environment applications
04 For high-speed applications
05 For micro-oscillation applications

Lubrication oil:
For general applications, ISO V32-68

Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.

General Data

Lubrication Syringe

LUB - 01 - 18G

Lubricant
Lubrication grease:
00 (For general applications)
01 (For low-friction, low-noice applications)
02 (For clean room applications)
03 (For clean room and vacuum enviromen applicatioin)
04 (For-high speed applications)
05 (For micro-oscillation applications)
Lubrication oil:
11 (For general applications, ISO V32-68)

Needle model
21G (5M/5W)
19G (7M/7W)
18G (9M/9W/12M/12W)
15G (15M / 15W)

Designation	Compatible with	Lubricant	Needle model
LUB-00-21G	MR5/MR5W	00, for general applications	21G
LUB-00-19G	MR7/MR7W	00, for general applications	19G
LUB-00-18G	MR9/MR9W	00, for general applications	18G
LUB-04-18G	MR12/MR12W	04, for high-speed applications	18G
LUB-00-15G	MR15/MR15W	00, for general applications	15G

Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.