SBI FV

Super short block with flange. Side nipple, dustproof end seal and self-lubricant container end seal as option.

* S: Bolt size for bottom mounting type of block



All blocks and rails are also available in Raydent treated material:
• Corrosion resistant
• Patented black surface
• Balls of stainless steel available as option


Please contact Rollco for more information.

Dimensions in mm.

Lead times in the table below are only indications. Choice of preload and other options will affect lead time. Please contact us for exact delivery time for your request.

Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.

General Data




Designation	Dynamic Load Capacity C (N)	Static Load Capacity C0 (N)	Static Moment Mr0 (Nm)	Static Moment Mp0 (Nm)	Static Moment My0 (Nm)
SBI15FV	5800	12800	40	30	30
SBI20FV	9400	20200	120	100	100
SBI25FV	12400	26100	190	170	170

Designation	Dynamic Moment Mr (Nm)	Dynamic Moment Mp (Nm)	Dynamic Moment My (Nm)	Weight Block (g)	Weight Rail (g/m)
SBI15FV	18	14	14	100	1300
SBI20FV	56	47	47	240	2200
SBI25FV	90	81	81	370	3000

Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.

Dimensions



Designation	L	H	W	W1	W2	L1	H1	h2	S1
SBI15FV	39.9	24	47	15	16	21.3	13	21	4.5
SBI20FV	49.1	28	63	20	21.5	27.1	16.5	23.4	4.8
SBI25FV	52.6	33	70	23	23.5	30.6	20	27.5	5.4

Designation	S2	D x d x g1	Hole Pitch (P)	N1	N2	N3	P2	E	G	M
SBI15FV	3.8	7.5 x 4.5 x 5.5	60	M4x0.7	Ø 3.5	3.4	38	5.5	20	M5
SBI20FV	4	9.5 x 6 x 8.5	60	M6x0.75	Ø 3.5	5	53	12	20	M6
SBI25FV	5.4	11 x 7 x 9	60	M6x0.75	Ø 3.5	5	57	12	20	M8

Designation	P	S	T	Length
SBI15FV	60	M4	8.8	3000
SBI20FV	60	M5	8	4000
SBI25FV	60	M6	9	4000

Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.