## **Adapter Plate for HK Clamping Element**

Because of the height difference of different rail guide blocks and to ensure the proper function of the HK Clamping Elements, the use of adapter plates is sometimes needed. See document "Selection of Clamping Elements" for individual block types and whether an adapter plate is needed.

Dimensions in mm.




## **General Data**

Designation	Weight (kg)
PHK15-4	0.033
РНК25-4	0.062
PHK30-3	0.08
PMK35-7	0.2
PHK45-10	0.39

Rollco Norge AS • Industrigata 6 • 3414 Lierstranda • Norge Tel. +47 32 84 00 34 • info@rollco.no • Org.nr 984 962 983 Page 2 of 3 Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.

h

## Dimensions



Designation	А	В	S2	E1	E2	E3	h
PHK15-4	47	24	M4	17	17	3.5	4
PHK25-4	70	30	M6	20	20	5	4
PHK30-3	90	39	M6	22	22	8.5	3
РМК35-7	100	39	M8	24	24	7.5	7
PHK45-10	120	44	M10	26	26	9	10

Rollco Norge AS • Industrigata 6 • 3414 Lierstranda • Norge Tel. +47 32 84 00 34 • info@rollco.no • Org.nr 984 962 983 Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.