Hinge System with Adjustable Friction

For surface elements and aluminium profiles; catch holds doors and flaps at any angle.

Infinitely adjustable at 0–5 Nm torque; can also be used to lift lightweight flaps.

Material: Wing = Plastic (PA), fibreglass reinforced; Pin = Stainless steel


On-site mount


Slot 6 mount: 4× M6 × 12 cheese head screw (DIN6912) 4× slot nut-Colour: Black


System: 30 - Slot 6 Type: Hinges












Rollco Norge AS • Industrigata 6 • 3414 Lierstranda • Norge Tel. +47 32 84 00 34 • info@rollco.no • Org.nr 984 962 983 Page Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice

General Data



System hinge 30

Designation	Description	System	FAmax (N)	FRmax (N)	Friction Torque (Nm)
PZ5291	Hinge system 30 with adjustable friction	30 - Slot 6	325	400	0-5

Rollco Norge AS • Industrigata 6 • 3414 Lierstranda • Norge Tel. +47 32 84 00 34 • info@rollco.no • Org.nr 984 962 983 Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.