Central Fastener 40 90°

Application:


Fastener for 90° mitered joint, cut angle is 45°


Assembly:


Bore hole for the barrel housing (2x): Ø 12 mm, 38 mm from profile end, 30 mm deep.

Bore for center hole on end of profile for anchor (2x): Ø 8.5 mm, 50 mm deep; Ø 10 mm, 26 mm deep.

System: 40 - Slot 8 Type: Fasteners







Rollco Norge AS • Industrigata 6 • 3414 Lierstranda • Norge Tel. +47 32 84 00 34 • info@rollco.no • Org.nr 984 962 983 Page 1 of 2 Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.

General Data

Designation	Description	System	Material	Weight (g)
SV1650V	Central Fastener 40 90°	40 - Slot 8	Steel, zinc-plated	42
SV1660V	Plastic Corner 40 90°	40 - Slot 8	POM, black	8

Rollco Norge AS • Industrigata 6 • 3414 Lierstranda • Norge Tel. +47 32 84 00 34 • info@rollco.no • Org.nr 984 962 983 Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.