

# Linear Unit CTV

CTV - 110 - 1610 - ISO7 - 0 - 700 - S - 2 - 200 - 1 - 1

**Series**

CTV

**Size**

90  
110  
145  
200

**Ball screw**

CTV 90: Ø12x5, Ø12x10  
CTV 110: Ø16x5, Ø16x10, Ø16x16  
CTV 145: Ø20x5, Ø20x10, Ø20x20, Ø20x50  
CTV 200: Ø32x5, Ø32x10, Ø32x20, Ø32x32

**Ball screw tolerance**

ISO7 (Standard)  
ISO5

**Ball screw journal\***

0: Without keyway  
1: With keyway

**Absolute stroke (mm)**

(Absolute stroke = Effective stroke + 2 x Safety stroke)

**Carriage version**

S: Short  
L: Long

**Number of carriages\*\***

The stated number specifies the number of carriages on one Linear unit (up to 5 carriages)  
Leave blank for the case of one carriage

**Distance between two carriages (mm)**

Leave blank for the case of one carriage

**Connection plate**

0: Without  
1: With

**Protection cover**

0: Without antistatic PU Gap-type seal strip  
1: With antistatic PU Gap-type seal strip (standard)  
2: With corrosion-resistant protection strip

\* CTV 90 only available without keyway - 0

\*\* Connection between the carriages is not rigid